


DuPont™ Tapes and Sealant

ACHIEVE OPTIMAL AIRTIGHTNESS AND LONG-TERM PERFORMANCE

The energy efficiency of domestic and non-domestic buildings is to a great extent dependent on the continuity of materials used in the building envelope. With an ever increasing requirement to conserve energy the portfolio of DuPont™ Tyvek® products can help you achieve these environmental goals.

The Tyvek® range of accessories has been developed to compliment and enhance building envelope solutions with Tyvek®. The range utilises adhesive tapes and sealants specifically designed



for use with Tyvek® membranes to help reduce uncontrolled air leakage through the building envelope.

The complete system works with the internal ventilation regime to allow a controlled flow of air in and out of a building, helping to maintain internal temperatures in both summer and winter and reduce energy costs.

Using genuine Tyvek® accessories will ensure compatibility with the Tyvek® system and guarantee long term performance and durability.

NEW



DuPont™ Universal Sealant (1210S)

Polyurethane (PU) sealant for all DuPont membrane overlaps, wood, PVC, concrete, brick/block and most plastics. Can be applied at low temperatures, suitable for internal or external use, resistant to water. Excellent aging and outdoor performance.

Colour: Grey

Cartridge size: 310ml

Cartridges per box: 12



Tyvek® Tape (2060B)

Single-sided tape for sealing overlaps and making good around penetrations, pipes and windows. Recommended for Tyvek® SD2, but suitable for all Tyvek® membranes. Made of Tyvek® and acrylic adhesive for durable and long lasting bonding.

Colour: White

Roll size: 75mm x 25m

Rolls per box: 6

NEW



Tyvek® Double Sided Tape (1310D)

Double sided acrylic tape ideal for sealing overlaps and bonding Tyvek® membranes to smooth surfaces. Excellent adhesion properties under extreme humidity conditions. Strong initial tack. Recommended for Tyvek® UV Facade, but suitable for all Tyvek® membranes.

Colour: Transparent

Roll size: 50mm x 25m

Rolls per box: 10



Tyvek® Metallised Tape (2060M)

Single-sided reflective tape for sealing laps in Tyvek® Enercor® Roof and Tyvek® Reflex / Tyvek® Enercor® Wall and DuPont™ AirGuard®. Ideal for making good around penetrations, pipework, windows and doors. Made of metallised Tyvek® and acrylic adhesive. Provides durable and long-lasting bond once cured.

Colour: Silver

Roll size: 75mm x 25m

Rolls per box: 6

NEW



Tyvek® UV Facade Tape (1310F)

Single sided acrylic tape with high UV resistance and excellent bonding properties. Especially designed for sealing Tyvek® UV Facade overlaps, penetration and joints in a durable and non-contrasting manner. Excellent aging and outdoor performance.

Colour: Black

Roll size: 75mm x 25m

Rolls per box: 8



Tyvek® Butyl Tape (1310B)

Double sided butyl based sealant, used to form a moisture and airtight seal between a Tyvek® membrane and most commonly used building materials. The product is compatible with brickwork, blockwork, masonry, timber, metalwork and most plastic products. Tyvek® Butyl Tape is most effective when used under compression, eg. under a timber batten and is recommended for use at perimeters, chimneys, abutments and for sealing nail penetrations and around electrical sockets.

Colour: Black

Roll sizes: 20mm x 30m

50mm x 30m

Rolls per box: 8 (20mm x 30m)

4 (50mm x 30m)



MAKE THE RIGHT CHOICE

Applications	Tyvek® Tape	Tyvek® Metallised Tape	Tyvek® Double Sided Tape	Tyvek® Butyl Tape	DuPont™ Universal Sealant	Tyvek® UV Facade Tape
Standard products						
Tyvek® Supro	✓		✓	✓	✓	
Tyvek® Framewrap	✓		✓	✓	✓	
Tyvek® Housewrap	✓		✓	✓	✓	
Tyvek® SD2	✓			✓	✓	
Special products						
Tyvek® Metal			✓	✓	✓	
Tyvek® UV Facade			✓	✓	✓	✓
DuPont™ Climate Systems						
Tyvek® Enercor® Roof	✓	✓	✓	✓	✓	
Tyvek® Reflex/Enercor® Wall		✓	✓	✓	✓	
DuPont™ AirGuard®		✓		✓	✓	
Materials						
Masonry/concrete/render (smooth)	✓	✓	✓	✓	✓	✓
Brick/block/concrete (rough)				✓	✓	
Plasterboard	✓	✓	✓	✓	✓	✓
Eaves Carrier			✓	✓	✓	
Window/door frames	✓	✓	✓	✓	✓	✓
Metal surface	✓	✓	✓	✓	✓	✓
Timber (rough sawn)				✓	✓	
Timber (planed)	✓	✓	✓	✓	✓	✓
Details						
Pipe penetrations (plastic)	✓	✓				✓
Pipe penetrations (metal)	✓	✓				✓
Wiring/cable penetrations	✓	✓				✓
Chimneys				✓	✓	
Chimneys (making good corners)	✓	✓				
Around electrical sockets	✓		✓	✓	✓	
Other						
Damage repair	✓	✓				✓
Nail penetration*				✓		
Making good	✓	✓				✓
Laps sealing	✓	✓	✓		✓	✓

* Under batten

DuPont Tyvek
29, Hither Green Trading Estate
Clevedon, North Somerset BS21 6XU
Tel: 01275 879 770
Fax: 01275 879 773
E-mail: tyvek.construction@dupont.com

www.construction.tyvek.com

All DuPont™ Tyvek® membranes have undergone extensive testing for the purposes of CE certification.

Copyright © 2009 DuPont. All rights reserved. The DuPont Oval, DuPont™, The miracles of science™ and Tyvek® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates.



The miracles of science™