



# Kooltherm®

## PRODUCT SAFETY INFORMATION

These products are exempt from the requirements of Article 57 and 59(1) of REACH Regulation (EC) No 1907/2006. The information below follows the SDS format as described in Annex 2 of the Regulation.

### 1 Identification of Products and Company

#### Products

Kingspan Kooltherm® K103 Floorboard  
Kingspan Kooltherm® K106 Cavity Board  
Kingspan Kooltherm® K107 Pitched Roof Board  
Kingspan Kooltherm® K108 Cavity Board  
Kingspan Kooltherm® K110 Soffit Board  
Kingspan Kooltherm® K110 PLUS Soffit Board  
Kingspan Kooltherm® K112 Framing Board  
Kingspan Kooltherm® K118 Insulated Plasterboard  
Kingspan Kooltherm® K5 External Wall Board  
Kingspan Kooltherm® K7 Pitched Roof Board  
Kingspan Kooltherm® K8 Cavity Board  
Kingspan Kooltherm® K9  
Kingspan Kooltherm® K10 FM Soffit Board  
Kingspan Kooltherm® K10 PLUS Soffit Board  
Kingspan Kooltherm® K12 Framing Board  
Kingspan Kooltherm® K15 Rainscreen Board  
Kingspan Kooltherm® K17 Insulated Plasterboard  
Kingspan Kooltherm® K18 Insulated Plasterboard  
Kingspan Kooltherm® Cavity Closer  
Kingspan Kooltherm® Duct Insulation  
Kingspan KoolDuct®

#### Company

Kingspan Insulation Limited  
Pembridge  
Leominster  
Herefordshire, HR6 9LA, UK  
Tel: +44 (0) 1544 388 601  
Fax: +44 (0) 1544 388 888  
Email: [info@kingspaninsulation.co.uk](mailto:info@kingspaninsulation.co.uk)  
Website: [www.kingspaninsulation.co.uk](http://www.kingspaninsulation.co.uk)

### 2 Hazards Identification

Not applicable.

### 3 Composition

**Core:** Rigid thermoset phenolic (as defined in EN13166) insulation.

**Alternative Facings:** Reinforced foil complex (K106, K110, K118, K10, K15, K17, K18, Duct Insulation).  
Composite foil (K107, K108, K112, K7, K8, K12).

Glass tissue (K103, K110, K110 PLUS, K118, K3, K5, K9, K10, K10 PLUS, K17, K18, Duct Insulation).  
Non-combustible building board (K110 PLUS, K10 PLUS)  
Polypropylene fleece (K106)  
Plasterboard (K118, K17, K18).  
PVC (Cavity Closer).

## 4 First-Aid Measures

- Inhalation:** Dust is non-hazardous.  
Remove the person to fresh air.
- Skin:** Non-sensitising.  
When facings containing glass fibres are handled, skin irritation may occur. Wash carefully using soap and water or a proprietary cleanser to remove.
- Eyes:** Dust particles should be removed by flushing with clean water.
- Ingestion:** No information available.
- Other:** Seek medical attention if discomfort persists.

## 5 Fire-Fighting Measures

It is prudent to take precautions against ignition, fire spread and smoke hazard.

**Suitable media:** Waterspray (fog), foam, CO<sub>2</sub> or dry chemical.

**Un-suitable media:** Not applicable.

Fire fighters should use self contained breathing apparatus and saturate burning foam with water from a spray nozzle. Dust is classified as weakly explosive (St. Class 1).

## 6 Accidental Release Measures

Not applicable.

## 7 Handling and Storage

Store in original packing in a location free from any ignition hazard such as open flames, cutting and welding torches, high surface temperature electric heaters and other forms of direct radiant heat.

Keep product protected from the elements. Ensure stability of stack and provide adequate aisle space for access between stacks.

## 8 Exposure Controls / Personal Protection

- Inhalation:** Dust is non-hazardous.  
As with all cutting procedures it is recommended that a disposable dust mask be worn.  
Where dust is generated through mechanical cutting in confined spaces, it is recommended that extraction be used.
- Hands:** It is recommended that gloves be worn when handling the products.
- Eyes:** Eye protection recommended during mechanical cutting.  
When installing a product with reflective foil facings in very bright or sunny weather it is advisable to wear UV protective sunglasses or goggles.
- Skin:** Non-sensitising.  
It is recommended to wear gloves when handling the products.  
When installing a product with reflective facings in bright sunlight, it is advisable to consider skin protection from UV.
- Other:** The products are non-load bearing.  
Access and work should not be carried out on un-supported boards.  
The smooth facing used on some Kooltherm products can be slippery underfoot when wet.

## 9 Physical and Chemical Properties

- Appearance:** Peach / yellow / brown foam with reinforced foil complex, composite foil, bitumen coated perlite, glass tissue, plasterboard or PVC facings.

<b>Odour:</b>	Negligible.
<b>pH:</b>	Neutral under normal conditions.
<b>Melting point:</b>	Not applicable.
<b>Flash point:</b>	Not applicable.
<b>Insulation density:</b>	Typically 30-60 kg/m <sup>3</sup> .
<b>Solubility in water:</b>	Insoluble.
<b>Solubility in organics:</b>	Some liquids might cause swelling.
<b>Other data:</b>	None.

## 10 Stability and Reactivity

Stable and un-reactive during normal use (see section 7).

## 11 Toxicological Information

No information available at this time.

## 12 Ecological Information

The products are inert and stable in water and soil.

## 13 Disposal Considerations

Waste insulation is non-hazardous.

Product dust created in the installation process is regarded as nuisance dust only, because of its inert nature.

Observe usual safety precautions with polythene bags, wrapping and packaging.

Clean, undamaged product may be re-used. Insulation core waste is fully recyclable.

Waste product should be disposed of in accordance with the Waste Hierarchy – Reduce, Re-Use, Recycle.

## 14 Transport Information

Read this section in conjunction with section 7.

Ensure security of load and where necessary sheeting / roping should be used.

It is recommended that mechanical lifting equipment is used when moving bulk quantities.

## 15 Regulatory Information

Not applicable.

## 16 Other Information

The information contained here is offered in good faith and is based on our current knowledge. We thereby withhold the right to update and amend this document as necessary.

The information should not be taken as guarantee of specific performance and users should make their own assessment and make all applicable personnel aware accordingly.

The wearing of appropriate safety equipment is strongly recommended as a precaution and the product should only be used in its design application.

Users should visit the Kingspan Insulation website or contact the Kingspan Insulation Technical Service Department to ensure information is current.



**Kingspan Insulation Ltd**

Pembridge, Leominster, Herefordshire HR6 9LA, UK  
Tel: +44 (0) 1544 388 601 Fax: +44 (0) 1544 388 888  
email: [info@kingspaninsulation.co.uk](mailto:info@kingspaninsulation.co.uk)

[www.kingspaninsulation.co.uk](http://www.kingspaninsulation.co.uk)