



SPECIFICATION CLAUSE

THIN-R^{PIR} INSULATION

Ground Supported & Suspended Floors

XT/PR_UF (FLOORS)

The floor insulation shall be Unilin Insulation Thin-R XT/UF manufactured to EN 13165 by Unilin Insulation, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings. The Thin-R XT/UF ___mm with an Agrément declared Lambda value of 0.022 W/mK to achieve a U-Value of ___ W/m²K for the floor element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause M10 290, M10 40, M13 260, M13 40, P10 250, P10 45.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

- BBA Certification No. 08/4613.
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Thin-R XT/UF Under Floor Insulation

Edge Profile

Square Edge

Face Size

2400mm x 1200mm

Thickness

25 mm / 30 mm / 40 mm / 50 mm / 60 mm / 70mm / 75mm / 80mm / 90mm / 100mm / 110mm / 125mm / 150mm

Other sizes available dependent on quantity & lead time.